

Model			MCLA09	MCA18
Refrigerant Type	R410A	g	1050	2000
Power Supply		Ph-V-Hz	1, 115V~, 60Hz	1, 208/230V ~60Hz
Cooling	Capacity	Btu/h	9000	18000
	Input	W	800	1560
	Rated Current	A	7.5	6.8
	SEER	Btu/w.h	13.0	13.0
Moisture Removal		L/h	0.9	1.55
Compressor	Brand		TOSHIBA	
	Rated Current	A	7.5	7.30/6.65
	Refrigerant Oil	ml	350	750
Indoor Air Flow (Hi/Mi/Lo)		m3/h	680/550/420	1050/920/830
Indoor Noise Level (Hi/Mi/Lo)		dB (A)	41/35/28	45/43/41
Outdoor Air Flow		m3/h	1800	2500
Outdoor Noise Level		dB (A)	53	59
Indoor Unit	Dimension (W*H*D)	mm	815*280*195	1250*325*230
	Packing (W*H*D)	mm	915*275*360	1345*430*335
	Net/Gross Weight	kg	11-Aug	18/25
Outdoor Unit	Dimension (W*H*D)	mm	780*250*540	845*335*695
	Packing (W*H*D)	mm	910*335*575	965*395*755
	Net/Gross Weight	kg	32/35	53/57
Design Pressure		Mpa	4.5	4.5
Refrigerant Piping	Liquid Side/Gas Side	inch	1/4" / 3/8"	1/4" / 1/2"
	Max. Ref. Pipe Length	m	10	10
	Max. Difference in Level	m	5	5
Thermostat Type			Electronic Control	
Operation Temp		°C	17-30	17-30
Ambient Temp		°C	18-45	18-45
Application Area		m <sup>2</sup>	14-21	30-40
Certificate			ETL	